



**auViss**  
www.auviss.com



## **Box Type CCD IP Camera**

True D/N, Wire/Wireless, PoE

### **AiP-200 Series**



#### **Key Features:**

- > Full D1 720x480 resolution for amazingly 30fps vivid imaging
- > Dual codec MPEG-4 SP & JPEG to suit all bandwidth levels
- > Advanced dual streaming transmission providing secondary viewing device different choice of compression codec
- > WiFi-ready for remote access from anywhere in the world
- > 3G, Smart phone & PDA surveillance
- > Centralizing all assets via 36Ch NVR & 16Ch CMS surveillance platform
- > Local recording to SD card against arbitrary network & remote storage failure
- > Seamless system integration by SDK resources

# SPECIFICATION

## VIDEO

Sensor	1/3" Sony Super HAD CCD
Video Standard	Dual streaming codec MPEG-4 SP, JPEG
Group of Picture (GOP)	I / IP, selectable 3 levels multiplier
Data Rate	Streaming 1: 32 kbps ~ 4 Mbps CBR, 1 ~ 10 levels VBR Streaming 2: 32 kbps ~ 320 kbps CBR, 1 ~ 10 levels VBR, max 15 fps
Sensor Matrix	720x480
Horizontal Resolution	Authentic Sony DSP empowering, 540 TV lines
Resolution & Frame Rate	
D1	720x480 / 720x576 30/25 fps
4CIF	704x480 / 704x576 30/25 fps
CIF	352x240 / 352x288 30/25 fps
QCIF	176x120 / 176x144 30/25 fps
Video Out	Composite: 1 x BNC, 75 ohm, 50 dB
Day / Night Illumination	Mechanical IR Cut Filter
Sensitivity	Minimum 0.1 Lux at hi-res, 0.05 Lux at mid-res, 0 Lux with ICR on
Full Screen	Yes
Imaging	
Contour Fine Tuning	Brightness (11 levels), contrast (11 levels), Hue (11 levels), Saturation (11 levels) AGC (on / off), BLC (on / off), AES (on / off), AWB

## AUDIO

Compression Format	ADPCM, bi-directional audio streaming
Audio Line Input / Output	1 x embedded microphone / 1 x RCA jack

## CPU MODULE

CPU	ARM 9, 32-bit RISC
RAM / ROM	64MB / 8MB

## ALARM

Alarm In / Relay Out	RS-485, 2 x In, 2 x Out, mini-DIN 9-pin
Video Analytics	Video Motion Detection (VMD), 3 selectable zones, 10 sensitivity levels
Triggering Reaction	E-Mail, FTP, SD Card
Pre / Post Alarm	5 / 10 sec

## NETWORK

Protocols	3GPP, DDNS, DHCP, FTP, HTTP, NTP, PPPoE, SMTP, TCP/IP, UDP, UPnP
Ethernet	10/100 Base-T, auto sensing, RJ-45
Wireless	IEEE 802.11b/g compliant (embedded, optional)
PoE	IEEE 802.3af compliant (embedded, optional)
User Group	10 user accounts simultaneously
Encryption	WEP 64 / 128-bit, WPA, PSK

## LOCAL RECORDING

SD Card Storage	VMD, IP Check, Network Status (wired connection only)
Format	AVI (MPEG-4 / JPEG)
Control	Playback, file management

## REMOTE RECORDING

Web Surveillance	Web browser, manual, VMD, AVI (MPEG-4 / JPEG), JPEG
Mobile Surveillance	3G, 3G Symbian, Smart phone mobile phone & PDA
Professional Surveillance	36Ch NVR Lite surveillance platform (Pro / CMS optional)

## GENERAL

Unit Configuration	Via web browser (reboot, factory default, time synchronization, OSD overlay)
Setting Management	Configuration values export & import
Authentication	ID, Password
Firmware	HTTP mode, remote update
Log Listing	System, VMD, Alarm
Regulatory Approval	CE, FCC, RoHS, WEEE

## MECHANICAL

Lens Type & Mounting	CS mount, DC Iris
Dimension (HxWxD)	58x65x131.5 mm
Weight	250 g (W/O PoE, WiFi module)

## ELECTRICAL

Input Voltage	DC 12V
Power Consumption	Wired: 450mA, 5.4W; Wireless: 550mA, 6.6W

## BROWSING REQUIREMENT

OS	Microsoft Windows 2000 / XP / 2003 / Vista
CPU	Intel Celeron 1.6 GHz, 256 MB RAM
Graphic	32 MB
Web Browser	Microsoft Internet Explorer 6.0 or above

## ENVIRONMENTAL

Operating	0°C ~ 45°C
Storage	-30°C ~ 60°C
Humidity	0 ~ 80% RH non-condensing

## PACKING LIST

Quantity	Component
1	IP Camera Main Unit
1	Power Adaptor
1	Bracket
1	Software CD
1	User's Manual
1	Quick Guide
1	Warranty Card

## ORDERING INFORMATION

AiP-200D	True Day/Night (ICR) IP Cam
AiP-200DE	W / PoE
AiP-200DW	W / WiFi IEEE 802.11b/g
System	NTSC / PAL
Power Plug	US / EU / UK / Latin America

## OPTIONAL

36Ch NVR Pro Surveillance Platform (Support Audio)
16Ch CMS Control Center (Support Audio)
Camera Lens / Housing / Bracket

 **Auviss Technology Co., Ltd**

7F-1, No.240, Sec.2, Datong Rd, Sijhih City, Taipei County, Taiwan  
Tel: +886-2-8691-9370  
Fax: +886-2-8691-9310  
Email: [marketing@auviss.com](mailto:marketing@auviss.com)  
Website: [www.auviss.com](http://www.auviss.com)

