

Indoor/Outdoor Camera Housing & Bracket

Pressure Aluminum Die Casting Outdoor Camera Housing



AH1000 Classical Type

Dimension: (L) 390mm X (W) 114mm X (H) 124mm

Window: (W) 82mm X (H) 68mm

12VDC/24VAC/110VAC/230VAC

Heater (Single/Double) Optional

CE / IP 66 / RoHS

Semi-Cable-Management System

W/AB-16 bracket



AH3000 Sunshield Type

Dimension: (L) 380mm X (W) 114mm X (H) 120mm

Window: (W) 68mm X (H) 53mm

12VDC/24VAC/110VAC/230VAC

Heater (Single/Double) Optional

Blower Optional

CE / IP67/ IP44 (Blower Optional) / RoHS

Bracket optional



AH5000 Functional Type

Dimension: (L) 450mm X (W) 135mm X (H) 158mm

Window: (W) 90.5mm X (H) 81mm

12VDC/24VAC/110VAC/230VAC

Heater (Single/Double) Optional

Blower Optional

CE / IP67/ IP44 (Blower Optional) / RoHS

Fully-Cable-Management System

W/AB-19 bracket



AH7000 Wide Window Type

Dimension: (L)406mm X (W)144.5mm X (H)108.5mm

Window: (W) 92mm X (H)76mm

12VDC/24VAC/110VAC/230VAC

Heater & Blower Optional

CE / IP67/ IP44 (Blower Optional) / RoHS

Bracket optional

General Purpose Outdoor Camera Housing



AH-806B	Indoor/Outdoor	
Material	Aluminum	
Color	Beige	
Dimension	140(W)X112(H)X400(L)mm	
Window	70(L)X70(W)	
Input Voltage	DC12V/24~240VAC	
Control Temperature	HEATER	BLOWER
	ON:15°C±3°C	ON:35°C±3°C
	OFF:25°C±3°C	OFF:25°C±3°C
Safety Certifications	CE,IP66	
Weight	1510g	
Packing	12PCS/CTN	



AH-801, AH-801S	Indoor/Outdoor	
Material	Aluminum	
Color	Beige	
Dimension	142(W)X115(H)X390/310(L)mm	
Window	74(L)X63(W)	
Input Voltage	DC12V/24~240VAC	
Control Temperature	HEATER	BLOWER
	ON:15°C±3°C	ON:35°C±3°C
	OFF:25°C±3°C	OFF:25°C±3°C
Safety Certifications	CE, IP66, RoHS	
Weight	1488g	
Packing	12PCS/CTN	



AH-805A	Indoor/Outdoor	
Material	Aluminum	
Color	Beige	
Dimension	120(W)X108(H)X410(L)mm	
Window	64(L)X53(W)	
Input Voltage	DC12V/24~240VAC	
Control Temperature	HEATER	
	ON:15°C±3°C	
	OFF:25°C±3°C	
Safety Certifications	CE,IP66, RoHS	
Weight	1600g	
Packing	12PCS/CTN	

Bracket for Housing (Fully-Cable Management)



AB-15

Fully-Cable Management

Aluminum

Beige

Dimension: 210mm

Max. Load: 10Kgs

For AH-805A, 806B Housing



AB-17

Fully-Cable Management

Aluminum Die Casting

Ivory White

Dimension: 205*95*111mm

Max. Load: 35.0Kgs

For AH3000 Housing



AB-18

Fully-Cable Management

Aluminum Die Casting

Beige

Dimension: 213*146*86mm

Max. Load: 15Kgs

For AH7000 Housing



AB-19

Fully-Cable Management

Aluminum Die Casting

Beige

Dimension: 266*95*111mm

Max. Load: 35Kgs

For AH5000 Housing

Bracket for Housing (Semi-Cable Management)



AB-12

Semi-Cable Management

Aluminum

Beige

Dimension: 240(L) mm

Max. Load: 10Kgs

For AH7000, 801, 801S, 805A, 806B



AB-16

Semi-Cable Management

Pressure Aluminum Die Casting

Ivory White

Dimension: 250(L) mm

Max. Load: 35Kgs

For AH3000 Housing

Bracket for Indoor/Outdoor Camera



AB-01

Aluminum bracket
Silver
138(H) x 120(Ø) mm
Max. Load: 5 KG



AB-02

Aluminum bracket
Silver
258(H) x 120(Ø) mm
Max. Load: 5 KG



AB-03

Aluminum bracket
Black/White
115(H) x 75(Ø) mm
Max. Load: 2KG



AB-03A

Aluminum bracket
Silver
120(H) x 80(Ø) mm
Max. Load: 4KG



AB-04

Aluminum bracket
Silver
285mm (L)
Max. Load: 10 KG



AB-05

Aluminum bracket
Silver
340mm (L)
Max. Load: 10 KG



AB-06A/B/C/D

Aluminum bracket
Silver
AB-06A: 130mm
AB-06B: 242x204mm
AB-06C: 305~465mm
AB-06D: 617~1004mm
Max. Load: 4KG